

IVG MONTREAL / 10

RWDM

Montreal/10



Medium duty mandrel built water discharge hose, widely used by industry, construction sites etc.

Tube: Black smooth SBR rubber.

Cover: Black smooth EPDM rubber.

Reinforcing: Plies of synthetic cord.

Temperature: -35 to +70 degrees Celsius.

Markings: IVG "water" green stripe, 10 bar W.P.

I.D. (mm)	O.D. (mm)	W.P. (psi)	B.P. (psi)	Weight (kg/mt)	Coil Lth (mt)
13.0	20.0	150	450	0.23	20
19.0	26.0	150	450	0.29	20
25.0	33.0	150	450	0.46	20
32.0	42.0	150	450	0.77	20
38.0	48.0	150	450	0.85	20, 120
45.0	55.0	150	450	1.01	20
51.0	61.0	150	450	1.12	20, 120
63.5	75.5	150	450	1.70	20, 60
76.0	87.0	150	450	1.79	20, 120
90.0	102.0	150	450	2.60	20
102.0	115.0	150	450	4.07	20
114.0	129.0	150	450	4.20	20
127.0	147.0	150	450	5.40	20
152.0	170.5	150	450	6.44	20

PHONE (06) 876 2994

FAX (06) 876 2993

Specifications subject to change without notice