

IVG TORONTO

RWST

Toronto



Heavy duty mandrel built water suction and discharge hose. Used in pumping applications where a rugged hard wearing hose is required.

Tube: Black smooth SBR rubber.

Cover: Black smooth EPDM rubber.

Reinforcing: Plies of synthetic cord, steel wire helix.

Temperature: -35 to +70 degrees Celsius.

Markings: IVG "water" green stripe, 10 bar W.P.

I.D. (mm)	O.D. (mm)	W.P. (psi)	B.P. (psi)	Weight (kg/m)	Coil Lth (m)
19.0	29.0	150	450	0.63	20
25.0	35.0	150	450	0.82	20, 60
32.0	42.0	150	450	0.98	20
38.0	49.0	150	450	1.28	20, 60
51.0	63.0	150	450	1.74	20, 60
63.5	75.5	150	450	2.39	20
76.0	88.0	150	450	2.53	20, 60
90.0	104.0	150	450	3.92	20
102.0	116.0	150	450	4.60	20, 60
114.0	131.0	150	450	5.77	20
127.0	145.0	150	450	7.23	20
152.0	172.5	150	450	10.30	20, 60
203.0	228.0	150	450	17.99	12
254.0	283.0	150	450	23.52	12
305.0	338.0	150	450	28.00	12

PHONE (06) 876 2994

FAX (06) 876 1 Specifications subject to change without notice